



**PRODUCT DETAILS –  
2.5mm 22mil Dryback  
Product**

|                        |  |
|------------------------|--|
| Product Type           | Luxury Vinyl Plank                           |
| Classification         | ASTM F3261-Grade 1, Type B-Embossed          |
| Overall Thickness      | 2.5mm (0.0984")                              |
| Wear Layer             | 22mil (0.55mm)                               |
| Edge Profile           | Beveled edge                                 |
| Surface Finish         | Polyurethane Matt Coating with Ceramic Beads |
| Embossing              | Deep Emboss                                  |
| Size                   | 7.36" W x 48.35" L (187x1228mm)              |
| Square Feet Per Carton | 42.02 SQFT/CTN                               |
| Pieces Per Carton      | 17 PIECES/Carton                             |
| Weight Per Carton      | 18.95 KGS/CTN 41.70 LBS/CTN                  |
| Carton Per Pallet      | 60 Cartons/PLT                               |
| Installation Method    | Glue down                                    |

**TECHNICAL PROPERTY**

|                                 |  |
|---------------------------------|--|
| Dimensional Stability           | ASTM F2199 - Passes - ≤0.1% / lineal ft. (305 mm)        |
| Curling                         | ISO 23999 - Passes - ≤2mm                                |
| Static Load                     | ASTM F970 - Passes - ≤0.002" (0.04mm)                    |
| Static Load Limit               | SIM Test - 1000 psi (0.02mm)                             |
| Residual Indentation            | ASTM F1914 - Passes - Average: ≤0.016" (0.4mm)           |
| Resistance to Chemicals         | ASTM F925-Passes-No more than a slight change in surface |
| Resistance to Heat              | ASTM F1514 - Passes - Average ΔE < 8.0                   |
| Resistance to Light             | ASTM F1515 - Passes - Average ΔE < 8.0                   |
| Critical Radiant Flux           | ASTM E648 - Passes - Class I: ≥ 0.45 W/Sq.cm             |
| Smoke Density                   | ASTM E662 - Passes - Flaming & Non Flaming ≤ 450         |
| VOCs/TVOCs, Formaldehyde        | CDPH/EHLB Method v1.2 Compliant                          |
| Substances of Very High Concern | REACH SVHC 191 - Passes - Per Substance: ≤0.1% w/w       |
| Heavy Metals                    | ASTM F963 - Passes                                       |
| Phthalates                      | ASTM D7823 - Passes - CPSC-CH-C1001-09.3                 |
| Fungi Resistance                | ASTM G21-15 - Passes                                     |
| IIC                             | ASTM E492 & ASTM E989 - Result: 62                       |

**SUSTAINABILITY**

|               |                                 |
|---------------|---------------------------------|
| Material      | 100% Virgin Vinyl               |
| Certification | VOC A+ & Floor Score® certified |

**SERVICE**

|            |   |
|------------|---|
| Warranties | 25 Years Residential/15 Years Light Commercial/5 Years Commercial |
|------------|---|

